

1.0~1.8t XF series mast: (pneumatic)

Type	Model	Max. fork height	Overall height			Free lift		Front Overhang		Tilt range		Capacity						
			Lowered	Extended		Without backrest	With backrest	Without backrest	With backrest	FwD	BwD	Load capacity at 500mm						
				Without backrest	With backrest							Single tire			Dual tire			
												1 / 1.5	1.75t	1t	1.5t	1.75t	1t	1.5t
		mm	mm	mm	mm	mm	mm	mm	(°)	(°)	kg	kg	kg	kg	kg	kg	kg	
Wide view mast	X15M200	2000	1495	2565	2855	155	155	405	410	6	12	1000	1500	1500	1750	1000	1500	1750
	X15M250	2500	1745	3065	3455	155	155	405	410	6	12	1000	1500	1500	1750	1000	1500	1750
	X15M270	2700	1845	3265	3655	155	155	405	410	6	12	1000	1500	1500	1750	1000	1500	1750
	X15M300	3000	1995	3565	3955	155	155	405	410	6	12	1000	1500	1500	1750	1000	1500	1750
	X15M330	3300	2145	3865	4255	155	155	405	410	6	12	1000	1500	1500	1750	1000	1500	1750
	X15M350	3500	2245	4065	4455	155	155	405	410	6	12	1000	1500	1500	1750	1000	1500	1750
	X15M370	3700	2395	4265	4655	155	155	405	410	6	12	1000	1500	1500	1750	1000	1500	1750
	X15M400	4000	2595	4600	4995	155	155	405	410	6	12	1000	1500	1650	1000	1500	1700	
	X15M430	4300	2745	4900	5295	155	155	405	410	6	6	950	1450	1600	950	1450	1650	
	X15M450	4500	2845	5100	5495	155	155	405	410	6	6	900	1400	1550	950	1400	1600	
	X15M470	4700	2945	5300	5695	155	155	405	410	6	6	850	1350	1500	900	1350	1550	
	X15M500	5000	3095	5600	5995	155	155	405	410	6	6	800	1300	1450	850	1300	1500	
	X15M550	5500	3345	6100	6495	155	155	405	410	6	6	/	/	/	750	1150	1300	
	X15M600	6000	3595	6600	6995	155	155	405	410	6	6	/	/	/	700	1050	1150	
	X15U200	2000	1560	2585	2945	975	615	405	410	6	12	1000	1500	1750	1000	1500	1750	
Wide view full free duplex mast	X15U250	2500	1810	3085	3445	1225	865	405	410	6	12	1000	1500	1750	1000	1500	1750	
	X15U270	2700	1910	3285	3645	1325	965	405	410	6	12	1000	1500	1750	1000	1500	1750	
	X15U300	3000	2010	3545	3905	1425	1065	405	410	6	12	1000	1500	1750	1000	1500	1750	
	X15U330	3300	2160	3885	4245	1575	1215	405	410	6	12	1000	1500	1750	1000	1500	1750	
	X15U350	3500	2260	4085	4445	1675	1315	405	410	6	12	1000	1500	1750	1000	1500	1750	
Wide view full free triplex mast	X15U370	3700	2360	4285	4645	1775	1415	405	410	6	12	1000	1500	1750	1000	1500	1750	
	X15U400	4000	2560	4585	4945	1975	1615	405	410	6	12	1000	1500	1650	1000	1500	1700	
	X15N400	4000	1970	4680	4955	1300	1025	420	425	6	6	900	1400	1550	950	1400	1600	
	X15N430	4300	2070	4980	5255	1400	1125	420	425	6	6	850	1350	1500	900	1350	1550	
	X15N450	4500	2120	5130	5455	1500	1175	420	425	6	6	800	1300	1450	850	1300	1500	
	X15N470	4700	2170	5380	5705	1585	1225	420	425	6	6	750	1250	1400	800	1250	1450	
	X15N500	5000	2270	5595	5955	1685	1325	420	425	6	6	700	1200	1350	800	1250	1450	
	X15N550	5500	2470	6095	6455	1885	1525	420	425	3	6	650	950	1050	750	1150	1300	
	X15N600	6000	2720	6795	7155	2100	1725	420	425	3	6	600	700	750	700	1050	1150	
	X15N650	6500	2870	7180	7455	2200	1925	420	425	3	6	/	/	/	550	800	900	
X15N700	7000	2970	7595	7955	2385	2025	420	425	3	6	/	/	/	400	550	650		

With sideshifter minus 150kg,with integral sideshifter minus 100kg

2.0~2.5t XF series mast: (pneumatic)

Type	Model	Max. fork height	Overall height				Free lift		Front Overhang	Tilt range		Capacity						
			Lowered	Extended		Without backrest	With backrest	Without backrest		With backrest	FwD	BwD	Load capacity at 500 mm					
				Without backrest	With backrest								Single tire				Dual tire	
													2.0t	2.5t	2.0t	2.5t		
		mm	mm	mm	mm	mm	mm	mm	(°)	(°)	kg	kg	kg	kg				
Wide view mast	X25M200	2000	1535	2660	3045	140	140	465	6	12	2000	2500	2000	2500				
	X25M250	2500	1785	3160	3545	140	140	465	6	12	2000	2500	2000	2500				
	X25M270	2700	1885	3360	3745	140	140	465	6	12	2000	2500	2000	2500				
	X25M300	3000	2035	3660	4045	140	140	465	6	12	2000	2500	2000	2500				
	X25M330	3300	2185	3960	4345	140	140	465	6	12	2000	2500	2000	2500				
	X25M350	3500	2285	4160	4545	140	140	465	6	12	2000	2500	2000	2500				
	X25M370	3700	2435	4360	4745	140	140	465	6	12	2000	2500	2000	2500				
	X25M400	4000	2635	4660	5045	140	140	465	6	12	2000	2450	2000	2500				
	X25M430	4300	2785	4960	5345	140	140	465	6	6	1950	2300	2000	2450				
	X25M450	4500	2855	5160	5545	140	140	465	6	6	1900	2150	1950	2300				
	X25M470	4700	2985	5360	5745	140	140	465	6	6	1850	2000	1900	2150				
	X25M500	5000	3135	5660	6045	140	140	465	6	6	1800	1850	1850	2000				
Wide view full free duplex mast	X25M550	5500	3385	6160	6545	140	140	465	3	6	/	/	/	1900				
	X25M600	6000	3635	6660	7045	140	140	465	3	6	/	/	/	1750				
	X25U200	2000	1560	2680	3045	880	510	465	6	12	2000	2500	2000	2500				
	X25U250	2500	1810	3180	3545	1130	760	465	6	12	2000	2500	2000	2500				
	X25U270	2700	1910	3380	3745	1230	860	465	6	12	2000	2500	2000	2500				
	X25U300	3000	2010	3680	4045	1330	960	465	6	12	2000	2500	2000	2500				
	X25U330	3300	2160	3980	4345	1480	1110	465	6	12	2000	2500	2000	2500				
	X25U350	3500	2260	4180	4545	1580	1210	465	6	12	2000	2500	2000	2500				
	X25U370	3700	2360	4380	4745	1680	1310	465	6	12	2000	2500	2000	2500				
	X25U400	4000	2560	4680	5045	1880	1510	465	6	12	2000	2450	2000	2500				
	X25N400	4000	2000	4700	5045	1300	955	480	6	6	1900	2350	1950	2450				
	Wide view full free triplex mast	X25N430	4300	2100	5000	5345	1400	1055	480	6	6	1850	2200	1900	2350			
X25N450		4500	2150	5230	5595	1470	1105	480	6	6	1800	2050	1850	2200				
X25N470		4700	2200	5380	5745	1520	1155	480	6	6	1750	1900	1800	2050				
X25N500		5000	2300	5680	6045	1620	1255	480	6	6	1700	1750	1800	2050				
X25N550		5500	2500	6180	6545	1820	1455	480	3	6	1300	1400	1600	1900				
X25N600		6000	2750	6780	7095	2070	1705	480	3	6	1200	1400	1600	1750				
X25N650		6500	2900	7200	7545	2200	1855	480	3	6	/	/	/	1450				
X25N700		7000	3050	7680	8045	2370	2005	480	3	6	/	/	/	1150				

With sideshifter minus 150kg,with integral sideshifter minus 100kg

3.0~3.5t XF series mast: (pneumatic)

Type	Model	Max. fork height
------	-------	------------------

Simple/ Solid/ Smart


In the new XF Series, Hangcha brought together the experience of more than 30 years building forklifts and the latest forklift technologies, the result is superior in efficiency, environmental friendliness, comfortable operation, reliability, safety. The XF Series, produced from careful research and development, represent a true solution to needs from environment, operator and owner.



Productivity

Dynamic load sensing hydraulic steering system, Efficiency lighting system, lower fuel consumption, combine to provide increased productivity and reduced operating costs.

The new Dynamic load sensing hydraulic steering system contributes to reduce loss of hydraulic and improve energy efficiency.




Hydraulic oil balanced temperature (2.5T 4TNE98)


The new efficiency lighting system employs LED illuminant and new type reflector to reduce energy consumption, improve significantly illumination performance and prolong work time.



By optimizing transmission design, the power train provides higher efficiency. The fuel consumption is reduced by 10%.



Fuel consumption



Speed at full load (2.5T 4TNE98)

Environmental Friendliness

A lineup of powerful and clean engines and environment friendly materials help to reduce the output of undesirable substances over the lifetime of the truck, while creating a cleaner work environment.



Each model employs a specially developed engine for the optimum balance of power and superior environmental performance. All engines are in compliance with EU stage-III control regulation.

The environment friendly materials, such as nonasbestos brake shoe and new type sealing gasket, are adopted entirely to pursue environmental safety.

Comfortable Operation



In developing the new XF Series, comfort and ease of operation is carefully considered, for example, to improve vibration levels, compound engine damper and full floating power train are adopted. Comfortable operating environments for operator also contribute to increased productivity.



In addition to rubber damper between frames and steering axle, compound engine damper and full floating power train achieve flexible connection between frames and driving system, as a result, traveling vibrations and vibrations from the driving system are significantly reduced.



The enlarged capacity of optimized exhaust muffler, the intake muffler and the noise shield technologies provide significantly lower noise levels.

1. The new, relocated easy- to-see LCD meter lets the operator check on all aspects of operational status at a glance.
2. The new automobile-style light/turn-signal lever and forward-reverse lever are ergonomically designed and arranged to improve comfort and productivity.
3. The small diameter steering wheel with tilt adjustment provides the ideal operating position. The superior responsiveness of the steering wheel optimizes maneuverability even in narrow spaces.
4. The parking brake is specially developed. The operational force is reduced by 30%.
5. The automobile-style suspended pedals provide more ergonomic operation.




Comfortable Operation

Optimal visibility in all directions create the best conditions for high productivity through relaxed and safe working.




The extra foot space is provided to reduce operator fatigue significantly. The new wide-open, non-slip step makes getting in and out easy and safe.

The optional Electro-hydraulic proportional control system contributes more sensitive and precise load handling. The easy- to-operate levers provide total load handling operation. An armrest is provided to reduce fatigue.



In addition to the soft landing system, the soft lifting system is adopted (front lifting cylinders of triplex mast and full free duplex mast), as a result, the noise and shock of the mast significantly decreases.



The developed front lifting cylinders with smaller outer diameter give the operator superior forward visibility.

The double lifting cylinders provide better forward visibility.



Reliability

By focusing on enhancing reliability, reducing downtime, the XF series is able to make the greater productivity for customer.



The new aluminum alloy transmission with full floating structure features excellent heat dissipation capability, more and thicker disc meet the most demanding applications.



The new vehicle controller integrates all electrical components, features excellent durability for temperature, water and vibration for most demanding operation.



The new stamped air cleaner featuring tangential intake, double seal with safety filter is durable, corrosion-free and vibration-resistant, provides better filter efficiency and lower intake resistance than the previous.



XF series features rugged design, stamped frame and engine hood, stamped instrument panel and head guard, heavy profile rail mast combine to provide excellent rigidity, which ensures outstanding reliability even in heavy-duty work.



Extra capacity combined radiator with serpentine wave and optimized heat dissipation channel enhance the heat dissipation capability to keep engine reliability even in heavy-duty applications.

Easy Maintenance



Careful design facilitates inspection and servicing. Easy maintenance reduces the amount of downtime and helps to reduce cost also.

The cover on the Panel can be lifted up simply to check the brake fluid.

The two-piece design makes the floorboard easy to lift and remove for access to the power train.

The easy-to-operate latch provides quick access to the engine compartment.

The fasteners of the radiator cover can be turned easily by hand to enable quick inspections or servicing.

Safety

A wide range of technologies are applied to ensure absolute safety for both the operator and those in the surrounding.



The locking device of the engine hood damper and parking brake help add to safety.



An optional rear-pillar assist grip with a horn button enhances safety of operator while traveling in reverse.



- 1. The operator presence sensing system incorporates lifting/tilting and traveling locking function. When the operator leaves the seat, the system automatically locks lifting / tilting and disables traveling to ensure safety.
- 2. A throttling device is adopted to avoid the mast being out of control even some pipes are broken.

Standards

Transmission	Steering	Chassiss	Control	Hydraulic
/ Suspended transmission / Oil filter / Dipstick / Oil cooler / Non-asbesttos brake	/ Full hydraulic power steering / Smaller diameter steering wheel / Adjuster of steering wheel	/ Skidproof pedal / Rubber pedal / Engine hood spring	/ Power steering / Suspension pedal / Integrated combination switch / Cable parking brake	/ Dynamic load sending control valve (Diesel IC) / Hydraulic oil filter / Tilt cylender self-locking valve / Hydraulic oil dipstick
Truck	Power	Electronics	Mast	
/ Traction device / Handhilds / Standard seat / Standard overhead guard / Waterproof cover on the guard / Back view mirror / Pneumatic tyres / Toolbox	/ Big capacity aluminum radiator / Little tank / Whirlwind air cleaner / Safety filter / High-efficient intake muffler / High-efficient exhaust muffler	/ High-efficient front lights / High-efficient LED rear lights / Service-free start battery / Combination controller / LCD display / Neutual switch / Timee meter / Fuel gauge / Water temperature gauge / Pre-heat indicator / Charging indicator / Engine fuel pressure warning / Transmission oil pressure warning / Horn / Reversing uzzer / Power off	/ Standard wide view duplex mast / Standard forks / Standard fork carriage / Standard load back rest / Mast speed limiting valve / Load safety valve / Mast down buffer device / Mast up buffer device / Side roller	

Options

Truck	Transmission	Power	Hydraulic	Electronics	Mast
/ Cabin / Cabin heater / Front window / Super elastic tyre / No-mark tyre (white/green) / Suspension seat / Extinguisher / Cover of tilt cylender / Heightening overhead guard / Reversing assist grip / Special given color / Seat with sensing system / Boot for tilt cylinder / Counter weight net	/ 2-D wheel / Wet brake system	/ Duel fuel LPG system / Big capacity copper radiator / High-positioned exhaust system / Middle-positioned exhaust system / Air pre-cleaner / Net cover of radiator / Sparkle arrester / Purified exhaust system / Swiwel LPG bottle support / Downward LPG bottle support / Fan protector	/ Auxiliary hydraulic valve / Electro-hydraulic proportional control system / Return oil filter	/ OBD / Front working light / Rear working light / Warning lamp / Oil-water seperator warning	/ Duplex wide view free-lift mast / Triplex wide view free-lift mast / Triplex wide view 4-cylinder free-lift mast / Special forks / Wider fork carriage / Wider load back rest

Optional Attachments

- / Paper roll clamp

/ Rotating bale clamp

/ Load stabilizer

/ Multi-drum clamp

/ Bale clamp

/ Drum clamp

/ Dumping clamp

/ Crane arm

/ String Pole
- / Sideshifter

/ Rotating forks

/ Fork extensioner

/ Load release device

/ Carton clamp

/ Push-pull device

/ Bucket

/ Hook

/ Lengthened fork



XF series 1.0-1.8t forklift specification :

Distinguishing mark	1.1	Manufacturer		HANGCHA GROUP CO.,LTD.																	
	1.2	Manufacturer's type designation		CPCD10-XW32F/B/M	CPQD10-XW21F/B/M	CPCD10-XW10F	CPCD15-XW32F/B/M	CPYD15-XW51F/B/M	CPQD15-XW21F/B/M	CPYD15-XW21F/B/M	CPQYD15-XW21F/B/M	CPCD15-XW10F	CPCD18-XW32F/B/M	CPYD18-XW51F/B/M	CPQD18-XW21F/B/M	CPYD18-XW21F/B/M	CPQYD18-XW21F/B/M	CPCD18-XW10F			
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas		Diesel	Gasoline	Diesel	Diesel	LPG	Gasoline	LPG	DUAL FUEL	Diesel	Diesel	LPG	Gasoline	LPG	DUAL FUEL	Diesel			
	1.5	Rated capacity/rated load	Q (kg)	1000			1500						1750								
	1.6	Load centre distance	c (mm)	500			500						500								
	1.8	Load distance, centre of drive axle to fork	x (mm)	405			405						405								
		Rear overhang	mm	375			405						430								
	1.9	Wheelbase	y (mm)	1475			1475						1475								
Weight	2.1	Service Weight	kg	2510			2650						2760								
	2.2	Axle loading, laden front/rear	kg	3055/455			3660/490						3995/520								
	2.3	Axle loading, unladen front/rear	kg	1260/1250			1240/1410						1225/1540								
Tyres, chassis	3.2	Tyre size, front		6.50-10-10PR			6.50-10-10PR						6.50-10-10PR								
	3.3	Tyre size, rear		5.00-8-10PR			5.00-8-10PR						5.00-8-10PR								
	3.6	Tread, front	b ₁₀ (mm)	900			900						900								
	3.7	Tread, rear	b ₁₁ (mm)	920			920						920								
Dimensions	4.1	Tilt of mast/fork carriage forward/backward	α/β(°)	6/12			6/12						6/12								
	4.2	Height, mast lowered	h ₁ (mm)	1995			1995						1995								
	4.3	Free lift	h ₂ (mm)	155			155						155								
	4.4	Lift	h ₃ (mm)	3000			3000						3000								
	4.5	Height, mast extended	h ₄ (mm)	3955			3955						3955								
	4.7	Height of overhead guard (cabin)	h ₆ (mm)	2125(2205*)			2125(2205*)						2125(2205*)								
	4.20	Length to face of forks	l ₂ (mm)	2255			2285						2310								
	4.21	Overall width	b ₁ (mm)	1080			1080						1080								
	4.22	Fork dimensions	s/e/l (mm)	920×100×35			920×100×35						920×100×35								
	4.31	Ground clearance, laden, below mast	m ₁ (mm)	115			115						115								
	4.32	Ground clearance, centre of wheelbase	m ₂ (mm)	140			140						140								
	4.35	Turning radius	W _a (mm)	1965			1990						2015								
		Min. right angle stacking aisle width (Add load length and clearance)	mm	2370			2395						2420								
Performance data	5.1	Travel speed, laden/unladen	km/h	(-/19)(-/19.3)(-/19)	(-/18)(-/18)(-/18)	-/19	(-/19)(-/19.3)(-/19)	(-/18)(-/18)(-/18)	(-/18)(-/18)(-/18)			-/19	(-/19)(-/19.3)(-/19)	(-/18)(-/18)(-/18)	(-/18)(-/18)(-/18)			-/19			
	5.2	Lift speed, laden/unladen	m/s	0.580/-	0.510/-	0.610/-	0.580/-	0.510/-	0.510/-			0.610/-	0.580/-	0.510/-	0.510/-			0.610/-			
	5.3	Lowering speed, laden/unladen	m/s	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-			0.500/-	0.500/-	0.500/-	0.500/-			0.500/-			
	5.5	Drawbar pull, laden/unladen	N	(14600/-)(14400/-)(14100/-)	(14800/-)(14600/-)(14300/-)	15500/-	(14600/-)(14400/-)(14100/-)	(14800/-)(14600/-)(14300/-)	(14800/-)(14600/-)(14300/-)			15500/-	(14600/-)(14400/-)(14100/-)	(14800/-)(14600/-)(14300/-)	(14800/-)(14600/-)(14300/-)			15500/-			
	5.7	Gradeability, laden/unladen*	%	(40/-)(39/-)(38/-)	(41/-)(40/-)(39/-)	41/-	(33/-)(33/-)(32/-)	(34/-)(33/-)(33/-)	(34/-)(33/-)(33/-)			34/-	(30/-)(30/-)(29/-)	(31/-)(30/-)(30/-)	(31/-)(30/-)(30/-)			31/-			
Combustion-engine	7.1	Engine manufacturer/type		YANMAR/4TNE92	GCT(NISSAN)/K21	ISUZU C240NKFC01	YANMAR/4TNE92	GCT(NISSAN)/K21LPG	GCT(NISSAN)/K21			ISUZU C240NKFC01	YANMAR/4TNE92	GCT(NISSAN)/K21LPG	GCT(NISSAN)/K21			ISUZU C240NKFC01			
		Emission STD		StageIIIA/Tier3		StageIIIA/GB3	StageIIIA/Tier3					StageIIIA/GB3	StageIIIA/Tier3					StageIIIA/GB3			
	7.2	Engine power according to DIN ISO 1585	kw	32.8	31.5	35.4	32.8	29	31.5			35.4	32.8	29	31.5			35.4			
	7.3	Rated speed	min	2450	2300	2500	2450	2250	2300			2500	2450	2250	2300			2500			
	7.4	Number of cylinders/displacement	(-)/(cm ³)	4/2659	4/2065	4/2369	4/2659	4/2065	4/2065			4/2369	4/2659	4/2065	4/2065			4/2369			
	7.10	Battery voltage/nominal capacity	V/Ah	12/60	12/60	12/60	12/60	12/60	12/60			12/60	12/60	12/60	12/60			12/60			
		Rated torque	N·m/r/min	142/1600	144/1600	139.9/1800	142/1600	140/1600	144/1600			139.9/1800	142/1600	140/1600	144/1600			139.9/1800			
		Bore × stroke	mm	92x100	89x83	86x102	92x100	89x93	89x83			86x102	92x100	89x83	89x83			86x102			
		Transmissions Manufacturer		HANGCHA/OKAMURA/MS			HANGCHA	HANGCHA/OKAMURA/MS						HANGCHA	HANGCHA/OKAMURA/MS						HANGCHA
		Transmissions Type		Powershift																	
	Stage FWD/RVS		1/1																		
Addition data	10.1	Operating pressure for attachments	bar	145																	
	10.4	Fuel tank capacity	liter	50	50	50	50	28	50	28	50	50	50	28	50	28	50	50			

Note: *With suspension seat or cabin

* As a calculated value

XF series 2.0~2.5t forklift specification :

Distinguishing mark	1.1	HANGCHA GROUP CO.,LTD.																												
	1.2	CPCD20-XW33F/B/M	CPYD20-XW52F/B/M	CPQD20-XW22F/B/M	CPYD20-XW22F/B/M	CPQYD20-XW22F/B/M	CPCD20-XW32F	CPYD20-XW51F	CPQD20-XW21F	CPYD20-XW21F	CPQYD20-XW21F	CPCD20-XW43F/B	CPCD20-XW55F/B	CPCD20-XW56F/B/M	CPCD20-XW10F	CPCD25-XW33F/B/M	CPYD25-XW52F/B/M	CPQD25-XW22F/B/M	CPYD25-XW22F/B/M	CPQYD25-XW22F/B/M	CPCD25-XW32F	CPYD25-XW51F	CPQD25-XW21F	CPYD25-XW21F	CPQYD25-XW21F	CPCD25-XW43F/B	CPCD25-XW55F/B	CPCD25-XW56F/B/M	CPCD25-XW10F	
	1.3	Diesel	LPG	Gasoline	LPG	DUAL FUEL	Diesel	LPG	Gasoline	LPG	DUAL FUEL	Diesel	Diesel	Diesel	Diesel	Diesel	LPG	Gasoline	LPG	DUAL FUEL	Diesel	LPG	Gasoline	LPG	DUAL FUEL	Diesel	Diesel	Diesel	Diesel	
	1.5	2000														2500														
	1.6	500														500														
	1.8	465														465														
		415														490														
	1650														1650															
Weight	2.1	3405														3765														
	2.2	4705/700														5475/790														
	2.3	1610/1795														1560/2205														
Tyres, chassis	3.2	7.00-12-12PR														7.00-12-12PR														
	3.3	6.00-9-10PR														6.00-9-10PR														
	3.6	965														965														
	3.7	973														973														
Dimensions	4.1	6/12														6/12														
	4.2	2035														2035														
	4.3	140														140														
	4.4	3000														3000														
	4.5	4045														4045														
	4.7	2135(2215*)														2135(2215*)														
	4.20	2530														2605														
	4.21	1155														1155														
	4.22	1070x122x40														1070*122*40														
	4.31	115														115														
	4.32	150														150														
	4.35	2180														2245														
		2645														2710														
Performance data	5.1	(-/18.2)(-/18.6) (-/17.9)	(-/19)(-/19.4) (-/18.7)	(-/19)(-/19.4)(-/18.7)			-/19.4	-/18.2	-/18.2		(-/18.2)(-/18.6)	(-/18.2)(-/18.6)	(-/17.5)(-/18)	-/19.7	(-/18.2)(-/18.6) (/17.9)	(-/19)(-/19.4) (-/18.7)	(-/19)(-/19.4)(-/18.7)			-/19.4	-/18.2	-/18.2		(-/18.2)(-/18.6)	(-/18.2)(-/18.6)	(-/17.5)(-/18)	-/19.7			
	5.2	0.620/-	0.560/-	0.560/-			0.600/-	0.490/-	0.490/-		0.620/-	0.620/-	0.620/-	0.590/-	0.620/-	0.560/-	0.560/-			0.600/-	0.490/-	0.490/-		0.620/-	0.620/-	0.620/-	0.590/-			
	5.3	0.500/-	0.500/-	0.500/-			0.500/-	0.500/-	0.500/-		0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-	0.500/-			0.500/-	0.500/-	0.500/-		0.500/-	0.500/-	0.500/-	0.500/-			
	5.5	(19800/-)(19400/-) (19500/-)	(18700/-)(18300/-) (18400/-)	(18700/-)(18300/-)(18400/-)			14300/-	14500/-	14500/-		(19800/-) (19400/-)	(19800/-) (19400/-)	(19800/-)(19400/-) (19500/-)	15000/-	(19800/-)(19400/-) (19500/-)	(18700/-)(18300/-) (18400/-)	(18700/-)(18300/-)(18400/-)			14300/-	14500/-	14500/-		(19800/-)(19400/-) (19500/-)	(19800/-)(19400/-) (19500/-)	(19800/-)(19400/-) (19500/-)	15000/-			
	5.7	(35/-)(34/-)(34/-)	(33/-)(32/-)(32/-)	(33/-)(32/-)(32/-)			24/-	25/-	25/-		(35/-)(34/-)	(35/-)(34/-)	(35/-)(34/-)(34/-)	25/-	(30/-)(29/-)(29/-)	(28/-)(27/-)(27/-)	(28/-)(27/-)(27/-)			21/-	21/-	21/-		(30/-)(29/-)	(30/-)(29/-)	(30/-)(29/-)(29/-)	20/-			
		YANMAR/4TNE98	GCT(NISSAN)/K25LPG	GCT(NISSAN)/K25			YANMAR/4TNE92	GCT(NISSAN)/K21LPG	GCT(NISSAN)/K21		CUMMINS/QSF2.813NA49	mitsubishi/S45-Z362CSFL	YANMAR/4TNV94L-BXPHZ	ISUZU C240NKF01	YANMAR/4TNE98	GCT(NISSAN)/K25LPG	GCT(NISSAN)/K25			YANMAR/4TNE92	GCT(NISSAN)/K21LPG	GCT(NISSAN)/K21		CUMMINS/QSF2.813NA49	mitsubishi/S45-Z362CSFL	YANMAR/4TNV94L-BXPHZ	ISUZU C240NKF01			
	StagellIIA/Tier3					StagellIIA/Tier3				StagellIIA	StagellIIA	StagellIIA	StagellIIA/GB3	StagellIIA/Tier3					StagellIIA/Tier3				StagellIIA	StagellIIA	StagellIIA	StagellIIA/GB3				
Combustion-engine	7.2	42.1	35	38			32.8	29	31.5		36.5	35.3	34.6	35.4	42.1	35	38			32.8	29	31.5		36.5	35.3	34.6	35.4			
	7.3	2300	2400	2400			2450	2250	2300		2500	2250	2400	2500	2300	2400	2400			2450	2250	2300		2500	2250	2400	2500			
	7.4	4/3319	4/2488	4/2488			4/2659	4/2065	4/2065		4/2800	4/3331	4/3054	4/2369	4/3319	4/2488	4/2488			4/2659	4/2065	4/2065		4/2800	4/3331	4/3054	4/2369			
	7.10	12/90	12/60	12/60			12/90	12/60	12/60		12/90	12/90	12/90	12/90	12/90	12/60	12/60			12/90	12/60	12/60		12/90	12/90	12/90	12/90			
		186/1700	170/1600	185/1600			142/1600	140/1600	144/1600		186/1500	165/1700	191~208.5/1500	139.9/1800	196/1700	170/1600	185/1600			142/1600	140/1600	144/1600		186/1500	165/1700	191~208.5/1500	139.9/1800			
		98*110	89*100	89*100			92*100	89*83	89*83		94x100	94x120	94x110	86x102	98*110	89*100	89*100			92*100	89*83	89*83		94x100	94x120	94x110	86x102			
		HANGCHA/OKAMURA/MS					HANGCHA					HANGCHA/OKAMURA			HANGCHA/OKAMURA/MS	HANGCHA	HANGCHA/OKAMURA/MS					HANGCHA					HANGCHA/OKAMURA		HANGCHA/OKAMURA/MS	HANGCHA
		Powershift														Powershift														
		1/1														1/1														
	Addition data	10.1	175														175													
10.4		60	40	60	40	60	60	40	60	40	60	60	60	60	60	60	40	60	40	60	60	40	60	40	60	60	60	60		

XF series 3.0~3.5t forklift specification :

Distinguishing mark	1.1	Manufacturer	HANGCHA GROUP CO.,LTD.																											
	1.2	Manufacturer's type designation	CPCD30-XW33F/B/M	CPYD30-XW52F/B/M	CPQD30-XW22F/B/M	CPYD30-XW22F/B/M	CPQYD30-XW22F/B/M	CPCD30-XW43F/B	CPCD30-XW55F/B	CPCD30-XW56F/B/M	CPCD30-XW10F	CPCD35-XW33F/B/M	CPYD35-XW52F/B/M	CPQD35-XW22F/B/M	CPYD35-XW22F/B/M	CPQYD35-XW22F/B/M	CPCD35-XW43F/B	CPCD35-XW55F/B	CPCD35-XW56F/B/M											
	1.3	Drive: electric (battery or mains), diesel, petrol, fuel gas	Diesel	LPG	Gasoline	LPG	DUAL FUEL	Diesel	Diesel	Diesel	Diesel	Diesel	LPG	Gasoline	LPG	DUAL FUEL	Diesel	Diesel	Diesel											
	1.5	Rated capacity/rated load	3000										3500																	
	1.6	Load centre distance	500										500																	
	1.8	Load distance, centre of drive axle to fork	480										485																	
		Rear overhang	550										615																	
	1.9	Wheelbase	1700										1700																	
	Weight	2.1	Service Weight	4350										4705																
2.2		Axle loading, laden front/rear	6450/900										7255/950																	
2.3		Axle loading, unladen front/rear	1750/2600										1720/2985																	
Tyres, chassis	3.2	Tyre size, front	28*9-15-14PR										28*9-15-14PR																	
	3.3	Tyre size, rear	6.50-10-10PR										6.50-10-10PR																	
	3.6	Tread, front	1005										1005																	
Dimensions	3.7	Tread, rear	975										975																	
	4.1	Tilt of mast/fork carriage forward/backward	6/12										6/12																	
	4.2	Height, mast lowered	2050										2165																	
	4.3	Free lift	145										145																	
	4.4	Lift	3000										3000																	
	4.5	Height, mast extended	4145										4145																	
	4.7	Height of overhead guard (cabin)	2150(2230*)										2150(2230*)																	
	4.20	Length to face of forks	2730										2800																	
	4.21	Overall width	1225										1225																	
	4.22	Fork dimensions	1070*122*45										1070*122*50																	
	4.31	Ground clearance, laden, below mast	130										130																	
	4.32	Ground clearance, centre of wheelbase	165										165																	
	4.35	Turning radius	2355										2415																	
		Min. right angle stacking aisle width (Add load length and clearance)	2835										2900																	
	Performance data	5.1	Travel speed, laden/unladen	(-/17.2)(-/17.6)(-/17.6)		(-/17.9)(-/18.4)(-/18.3)		(-/17.9)(-/18.4)(-/18.3)		(-/17.2)(-/17.6)		(-/17.2)(-/17.6)		(-/18.6)(-/19)		(-/18.6)(-/19)		(-/17.2)(-/17.6)(-/17.6)		(-/17.9)(-/18.4)(-/18.3)		(-/17.2)(-/17.6)		(-/17.2)(-/17.6)		(-/18.6)(-/19)				
		5.2	Lift speed, laden/unladen	0.490/-		0.450/-		0.450/-		0.490/-		0.490/-		0.490/-		0.470/-		0.430/-		0.385/-		0.385/-		0.430/-		0.430/-		0.430/-		
		5.3	Lowering speed, laden/unladen	0.500/-		0.500/-		0.500/-		0.500/-		0.500/-		0.500/-		0.500/-		0.500/-		0.500/-		0.500/-		0.500/-		0.500/-		0.500/-		
5.5		Drawbar pull, laden/unladen	N (21000/-)(20500/-)(19900/-)		(19800/-)(19300/-)(18700/-)		(19800/-)(19300/-)(18700/-)		(21000/-)(20500/-)		(21000/-)(20500/-)		(20800/-)(20300/-)(19900/-)		16000/-		(21000/-)(20500/-)(19900/-)		(19800/-)(19300/-)(18700/-)		(21000/-)(20500/-)		(21000/-)(20500/-)		(20800/-)(20300/-)(19900/-)					
5.7		Gradeability, laden/unladen*	%		(27/-)(26/-)(25/-)		(25/-)(24/-)(23/-)		(25/-)(24/-)(23/-)		(27/-)(26/-)		(26/-)(25/-)		(27/-)(26/-)(25/-)		19/-		(24/-)(23/-)(22/-)		(22/-)(22/-)(21/-)		(24/-)(23/-)		(23/-)(22/-)		(24/-)(23/-)(22/-)			
Combustion-engine	7.1	Engine manufacturer/type	YANMAR/4TNE98		GCT(NISSAN)/K25LPG		GCT(NISSAN)/K25		CUMMINS/QSF2.813NA49		MITSUBISHI/S45-Z362CSFL		YANMAR/4TNV94L-BXPHZ		ISUZU C240NKF01		YANMAR/4TNE98		GCT(NISSAN)/K25LPG		GCT(NISSAN)/K25		CUMMINS/QSF2.813NA49		MITSUBISHI/S45-Z362CSFL		YANMAR/4TNV94L-BXPHZ			
		Emission STD	StageIIIA/Tier3								StageIIIA		StageIIIA/CB3		StageIIIA/Tier3												StageIIIA			
	7.2	Engine power according to DIN ISO 1585	kw		42.1		35		38		36.5		35.3		34.6		35.4		42.1		35		38		36.5		35.3		34.6	
	7.3	Rated speed	min		2300		2400		2400		2500		2250		2400		2500		2300		2400		2400		2500		2250		2400	
	7.4	Number of cylinders/displacement	(-)/(cm ³)		4/3319		4/2488		4/2488		4/2800		4/3331		4/3054		4/2369		4/3319		4/2488		4/2488		4/2800		4/3331		4/3054	
	7.10	Battery voltage/nominal capacity	V/Ah		12/90		12/60		12/60		12/90		12/90		12/90		12/90		12/90		12/60		12/60		12/90		12/90		12/90	
		Rated torque	N·m/r/min		196/1700		170/1600		185/1600		186/1500		165/1700		191~208.5/1500		139.9/1800		196/1700		170/1600		185/1600		186/1500		165/1700		191~208.5/1500	
		Bore × stroke	mm		98*110		89*100		89*100		94x100		94x120		94x110		86x102		98*110		89*100		89*100		94x100		94x120		94x110	
		Transmissions Manufacturer	HANGCHA/OKAMURA/MS										HANGCHA/OKAMURA		HANGCHA/OKAMURA/MS		HANGCHA		HANGCHA/OKAMURA/MS						HANGCHA/OKAMURA		HANGCHA/OKAMURA/MS			
		Transmissions Type	Powershift										Powershift																	
Addition data		Stage FWD/RVS	1/1										1/1																	
	10.1	Operating pressure for attachments	bar										175																	
	10.4	Fuel tank capacity	liter		40		70		40		70		70		70		70		40		70		40		70		70		70	

Note: *With suspension seat or cabin
* As a calculated value

